



# GMAX™ II ProConnect™ Optimum

Petrol-powered Airless Sprayers with integrated Hose Reel  
for Paint and Spack



www.graco.com

## OPTIMUM ADVANTAGES

- Integrated hose reel. Start your spraying job faster and go home sooner without the hassles of hose handling.
- Digital SmartControl™ monitors how you spray: delivers consistent spray fan without fluctuation at all spraying pressures.
- High performance, yet compact to spray a full range of coatings on residential, commercial and industrial jobs.

Heavy Duty Applications

**GMAX™ II 3900 PROCONNECT™ OPTIMUM - GMAX™ II 5900 HD PROCONNECT™ OPTIMUM -  
GMAX™ II 7900 HD PROCONNECT™ OPTIMUM**



# GMAX™ II ProConnect™ Optimum

Petrol-Powered Airless Sprayers

Welcome to a new world of Gas-Powered Airless Sprayers: GMAX II ProConnect™ OPTIMUM.

Graco® took the most demanded, highest quality Gas Sprayers and added features that Painting Contractors are asking for.

## OPTIMUM RANGE

The GMAX™ 5900 HD and 7900 HD (Heavy Duty) sprayers, are the answer for high production professional contractors who demand uninterrupted performance with freedom from electric power. True power horses (with respectively a 160 or 200 cc Honda engine) they can easily spray all thicker coatings as well as the whole range of primers and paints.

When used with a hopper or container suction kit, you can work for longer periods of time before refilling: perfect for larger amounts of material.

The GMAX™ II 3900 (120 cc) completes the line and is the perfect sprayer for the professional contractor working on new residential construction job sites.



## Endurance™ Piston Pump

Uniquely designed with oversized clearances to ensure minimal pressure drop. Long life Chromex™ rod, hardened SST Sleeve (3900/5900 HD) and V-Max Blue™ Packings. Unmatched durability with MaxLife™ sleeve on GMAX 7900 HD.



## SMARTCONTROL™

SmartControl delivers a consistent spray fan without pressure fluctuations through the full range from 30 to 230 bar. Complete with digital display, incorporating pressure, job/life time liter counter and self-diagnostics.



## Specially Designed Submerged Foot valve

The foot valve is placed low to the ground allowing submersion in the material bucket. The large ball allows maximal fluid passages to efficiently load thick and heavy materials. *(On 5900 HD and 7900 HD models only)*



## On-Board Tool Box

Convenient storage container for tools, tips, filters and accessories such as a second gun.

## Materials & Applications



The GMAX II ProConnect Optimum is the ideal unit to spray a full range of coatings on residential, commercial and industrial jobs. The 5900 HD and 7900 HD, handle most common tip sizes and heavier coatings with ease!

The GMAX II ProConnect Optimum sprays perfectly acrylics, primers, emulsions, waterborne and solvent based paints. The HD version also handles most common anti-corrosive and fire retardant paints and airless plasters.





PRO CONNECT



**ProConnect™**

ProConnect no-tools pump removal system allows you to replace your pump in seconds!  
- without any tools  
- on the job  
- quick and easy

**Heavy Duty Cart Design**

The proven design of cart and wheel make this powerful unit very easily transportable to the job-site.



**Hose Reel**

No need to explain the advantages. Roll on and off in a few seconds min. 45 m hose, giving an autonomy to spray in a range of min. 90 m without transporting the unit. Easy for transport, easy for storage! Holds: 90 m (1/4") / 60 m (3/8").

**Honda® Engine**

Compact and lightweight reliable motor technology, very easy to start. Comes with oil alert which helps to guarantee the optimal performance of the motor.

[www.graco.com](http://www.graco.com)

**GOOD TO KNOW**

**EXTEND YOUR SPRAYING AUTONOMY**

When used with a hopper or container suction kit, you can work for longer periods of time before refilling. Use for overnight storage or to transport your material. You will save energy, time and money.



**! TIP**

**ALWAYS BEGIN WORKING AT LOW MATERIAL PRESSURE.**

Slowly raise the pressure, but only to the minimum pressure required for a successful application. Using too much pressure can cause pack-out due to aggregated materials or dirt.

**MaxLife™ Technology**

Exclusive coating technology used on the piston rod and sleeve. Unmatched life. Drastically reduces maintenance costs.



**WatchDog™**



All GMAX II ProConnect OPTIMUM sprayers are standard equipped with the WATCHDOG PUMP PROTECTION SYSTEM, which automatically shuts the sprayer down when the bucket is empty. This will safeguard premature packing wear and extend the life of your pump.





# GMAX™ II ProConnect™ Optimum Accessories

Get the most out of your equipment, use our professional accessories

## Improve your spraying quality



### Guns

- 262114 Contractor™ airless gun, RAC X™ guard, no tip
- 289605 TexSpray™ blue gun with RAC X guard and RAC X 531 tip
- 245820 Inline™ 4-finger plaster gun, 280 bar

### Tips, Guards and Air Nozzles



- PAAXXX Blue RAC X tip for paint
- HDAXXX Brown RAC X tip for spack, heavy coatings
- WRXXX Wide RAC X tip for big surfaces, 120° angle
- 246215 RAC X guard

### RAC X Tip Extensions



- |        |       |        |       |
|--------|-------|--------|-------|
| 287019 | 25 cm | 287020 | 40 cm |
| 287021 | 50 cm | 287022 | 75 cm |

### CleanShot™ RAC X Pole Gun



- |        |       |        |        |
|--------|-------|--------|--------|
| 287026 | 90 cm | 287027 | 180 cm |
|--------|-------|--------|--------|

### Rollers Exterior (complete)



- 6880095 30 cm fixed
- 098084 90-180 cm telescopic
- 098085 45-90 cm telescopic

### Hoses (230 bar)



- |        |             |        |             |
|--------|-------------|--------|-------------|
| 240794 | 1/4" x 15 m | 240797 | 3/8" x 15 m |
| 223771 | 1/4" x 30 m | 241275 | 3/8" x 30 m |
| 241272 | 1/4" x 20 m |        |             |

### Whips (230 bar)



- 238358 3/16" x 0.9 m
- 238959 3/16" x 1.4 m
- 238359 3/16" x 1.8 m



### Gun, Tip, Hose Kits

- 288491 Contractor gun, 1/4" X 15 m hose, 3/16" x 0.9 m whip, RAC X PAA621 tip, 230 bar
- 289611 TexSpray blue gun, 3/8" X 15 m hose, 1/4" x 0.9 m whip, RAC X 531/427 tip, 230 bar
- 289585 Inline 4-finger plaster gun, 1/2" x 15 m hose, 3/8" x 3.6 m whip, RAC X 643 tip, 280 bar



### Hose Connectors

- 156971 1/4" x 1/4"
- 157350 1/4" x 3/8"

### Additional Accessories




- 287987 90 liter hopper kit
- 289587 Bag roller
- 24D415 Heavy duty container suction kit 40 cm 2" hose with 1" to DIN C clamp connectors.



### EasyOut™ Gun Filters

- 287032 EasyOut gun filter, 60 mesh x 1
- 287033 EasyOut gun filter, 100 mesh x 1
- 287034 Kit: 60 mesh x 1 + 100 mesh x 1



### EasyOut™ Pump Filters

- 244071 30 mesh, grey
- 244067 60 mesh, black
- 244068 100 mesh, blue
- 244069 200 mesh, red



### Liquids

- 206994 TSL™ 0.25 I
- 253574 Pump Armor™ 1 I
- 245133 Pump Armor 3.8 I

## GMAX II ProConnect Optimum

### READY TO GO,

The GMAX II ProConnect™ Optimum ships complete and ready to spray with hose reel, digital SmartControl™, WatchDog™, liter counter, error diagnosis, ProConnect, Endurance™ pump, toolbox, EasyOut™ filter, gun, RAC X™ guard and reversible airless tips, BlueMax™ II hose, TSL™, Pump Armor™.

Find this unit at:

## Specifications



	GMAX II 3900 ProConnect Optimum	GMAX II 5900 HD ProConnect Optimum	GMAX II 7900 HD ProConnect Optimum
<b>Part Numbers:</b>	<b>258731</b>	<b>258734</b>	<b>258735</b>
Max. Tip Size: 1 gun	0.035"	0.043"	0.047"
2 guns	0.023"	0.029"	0.035"
Flow - l/min. (gpm)	4.7 (1.25)	6.0 (1.6)	8.3 (2.2)
Max. pressure - bar (PSI)	230 (3300)	230 (3300)	230 (3300)
Max. hose length	45 m	60 m	75 m
Weight - kg (lbs)	50 (109)	64 (139)	67 (146)
Engine displacement Honda®:	120 cc	160 cc	200 cc
BlueMax II hose:	1/4" x 15 m	3/8" x 30 m	3/8" x 30 m
Gun:	Contractor - 2-finger	Blue texture	Blue texture
RAC X guard & tip:	LTX517	LTX 531/427	LTX 531/427
Rod:	Chromex	Chromex	Chromex
Sleeve:	Hardened SST	Hardened SST	MaxLife