

Serrated

Notes:-
 1. Deflection in the table above is limited to span/200 or 10mm, whichever is the lesser.
 2. It should be noted that the difference in level between a loaded and a neighbouring unloaded flooring shall not exceed 4mm. LK panel joint clips can be used to negate this issue. The below tables have both options listed.
 3. The below tables are based upon: BS4592-0:2006+A1:2012 & BS5950-1:2000 Table 2 Which is a 5kN/m² or 7.5kN/m² UDL OR a 1.5kN point load over a 200mmx200mm contact area, whichever is the more onerous.
 4. The below tables take into consideration MINIMUM bearing bar rolling tolerances as defined by LKFS-STD-98
 5. The patch load is placed on the centre of the panel for calculation purposes.
 6. Material is BS EN 10025 Grade S275JR

LOAD TABLE FOR N/100 (3MM BARS AT 30 CTRS)						
Bearing bar dimensions (mm)	Loading category	Max clear span for pedestrian loading categories	PATCH LOAD AT CENTRE OF PNL 4mm MAX DEF		PATCHLOAD AT CENTRE OF PNL - L/200 OR 10mm MAX DEF	
			Deflection (mm)	Max clear span for pedestrian loading categories	Deflection (mm)	
25 x 3	5kN/m ²	870	3.97	930	4.64	kN/m ²
	7.5kN/m ²	870	3.97	930	4.64	D (mm)
30 x 3	5kN/m ²	1070	3.98	1325	6.60	kN/m ²
	7.5kN/m ²	1060	3.99	1165	5.82	D (mm)
35 x 3	5kN/m ²	1270	3.97	1560	7.74	kN/m ²
	7.5kN/m ²	1200	3.99	1370	6.78	D (mm)
40 x 3	5kN/m ²	1465	3.95	1800	9.00	kN/m ²
	7.5kN/m ²	1335	4.00	1580	7.85	D (mm)

LOAD TABLE FOR E/100 (3MM BARS AT 33 CTRS)						
Bearing bar dimensions (mm)	Loading category	Max clear span for pedestrian loading categories	PATCH LOAD AT CENTRE OF PNL 4mm MAX DEF		PATCH LOAD AT CENTRE OF PNL - L/200 OR 10mm MAX DEF	
			Deflection (mm)	Max clear span for pedestrian loading categories	Deflection (mm)	
25 x 3	5kN/m ²	840	3.96	875	4.36	kN/m ²
	7.5kN/m ²	840	3.96	875	4.36	D (mm)
30 x 3	5kN/m ²	1035	3.99	1260	6.28	kN/m ²
	7.5kN/m ²	1035	3.99	1130	5.64	D (mm)
35 x 3	5kN/m ²	1230	3.99	1515	7.52	kN/m ²
	7.5kN/m ²	1170	3.95	1330	6.59	D (mm)
40 x 3	5kN/m ²	1425	3.97	1745	8.68	kN/m ²
	7.5kN/m ²	1305	4.00	1535	7.65	D (mm)

LOAD TABLE FOR W/100 (3MM BARS AT 41 CTRS)						
Bearing bar dimensions (mm)	Loading category	Max clear span for pedestrian loading categories	PATCHLOAD AT CENTRE OF PNL 4mm MAX DEF		PATCH LOAD AT CENTRE OF PNL - L/200 OR 10mm MAX DEF	
			Deflection (mm)	Max clear span for pedestrian loading categories	Deflection (mm)	
25 x 3	5kN/m ²	760	3.77	760	3.77	kN/m ²
	7.5kN/m ²	760	3.77	760	3.77	D (mm)
30 x 3	5kN/m ²	955	3.99	1090	5.44	kN/m ²
	7.5kN/m ²	955	3.99	1050	5.22	D (mm)
35 x 3	5kN/m ²	1135	4.00	1410	6.98	kN/m ²
	7.5kN/m ²	1110	3.97	1240	6.18	D (mm)
40 x 3	5kN/m ²	1315	3.98	1625	8.06	kN/m ²
	7.5kN/m ²	1235	3.97	1430	7.14	D (mm)

LOAD TABLE FOR N/100 (5MM BARS AT 30 CTRS)						
Bearing bar dimensions (mm)	Loading category	Max clear span for pedestrian loading categories	POINT LOAD AT CENTRE OF PNL 4mm MAX DEF		POINT LOAD AT CENTRE OF PNL - L/200 MAX DEF	
			Deflection (mm)	Max clear span for pedestrian loading categories	Deflection (mm)	
25 x 5	5kN/m ²	1150	4.00	1295	6.42	kN/m ²
	7.5kN/m ²	1040	3.92	1140	5.67	D (mm)
30 x 5	5kN/m ²	1330	3.96	1580	7.89	kN/m ²
	7.5kN/m ²	1210	3.97	1390	6.91	D (mm)
35 x 5	5kN/m ²	1505	3.98	1860	9.29	kN/m ²
	7.5kN/m ²	1370	3.98	1640	8.18	D (mm)
40 x 5	5kN/m ²	1670	3.98	2100	9.94	kN/m ²
	7.5kN/m ²	1520	3.96	1885	9.37	D (mm)
45 x 5	5kN/m ²	1830	3.98	2300	9.94	kN/m ²
	7.5kN/m ²	1670	4.00	2100	10.00	D (mm)
50 x 5	5kN/m ²	1985	4.00	2495	9.97	kN/m ²
	7.5kN/m ²	1810	3.98	2275	9.84	D (mm)
60 x 5	5kN/m ²	2275	3.97	2865	10.00	kN/m ²
	7.5kN/m ²	2080	3.98	2615	9.94	D (mm)

LOAD TABLE FOR E/100 (5MM BARS AT 33 CTRS)						
Bearing bar dimensions (mm)	Loading category	Max clear span for pedestrian loading categories	POINT LOAD AT CENTRE OF PNL 4mm MAX DEF		POINT LOAD AT CENTRE OF PNL - L/200 MAX DEF	
			Deflection (mm)	Max clear span for pedestrian loading categories	Deflection (mm)	
25 x 5	5kN/m ²	1115	3.96	1260	6.29	kN/m ²
	7.5kN/m ²	1020	3.97	1105	5.47	D (mm)
30 x 5	5kN/m ²	1300	3.94	1535	7.67	kN/m ²
	7.5kN/m ²	1185	3.99	1350	6.72	D (mm)
35 x 5	5kN/m ²	1470	3.95	1805	8.98	kN/m ²
	7.5kN/m ²	1340	3.98	1590	7.90	D (mm)
40 x 5	5kN/m ²	1635	3.98	2055	9.93	kN/m ²
	7.5kN/m ²	1490	3.99	1830	9.09	D (mm)
45 x 5	5kN/m ²	1790	3.97	2255	9.99	kN/m ²
	7.5kN/m ²	1630	3.96	2055	10.00	D (mm)
50 x 5	5kN/m ²	1940	3.96	2445	10.00	kN/m ²
	7.5kN/m ²	1770	3.97	2225	9.91	D (mm)
60 x 5	5kN/m ²	2230	3.98	2805	9.96	kN/m ²
	7.5kN/m ²	2035	3.97	2560	9.94	D (mm)

LOAD TABLE FOR W/100 (5MM BARS AT 41 CTRS)						
Bearing bar dimensions (mm)	Loading category	Max clear span for pedestrian loading categories	POINT LOAD AT CENTRE OF PNL 4mm MAX DEF		POINT LOAD AT CENTRE OF PNL - L/200 MAX DEF	
			Deflection (mm)	Max clear span for pedestrian loading categories	Deflection (mm)	
25 x 5	5kN/m ²	1020	3.96	1175	5.87	kN/m ²
	7.5kN/m ²	965	3.94	1030	5.11	D (mm)
30 x 5	5kN/m ²	1235	3.96	1430	7.11	kN/m ²
	7.5kN/m ²	1120	3.94	1255	6.21	D (mm)
35 x 5	5kN/m ²	1400	3.99	1685	8.38	kN/m ²
	7.5kN/m ²	1270	3.97	1485	7.42	D (mm)
40 x 5	5kN/m ²	1555	3.99	1940	9.67	kN/m ²
	7.5kN/m ²	1410	3.95	1710	8.55	D (mm)
45 x 5	5kN/m ²	1705	4.00	2140	9.92	kN/m ²
	7.5kN/m ²	1550	3.99	1930	9.58	D (mm)
50 x 5	5kN/m ²	1845	3.96	2325	9.99	kN/m ²
	7.5kN/m ²	1680	3.96	2115	9.96	D (mm)
60 x 5	5kN/m ²	2125	4.00	2670	9.96	kN/m ²
	7.5kN/m ²	1935	3.98	2435	9.98	D (mm)



UK:
 103 Airport Road West
 Belfast
 Co. Down
 BT3 9ED
 Tel: +44 (0) 28 90 454599

Ireland:
 Unit 1 & 2 Greene Park
 Ratoath Road
 Ashbourne
 Co. Meath
 A84 XD98
 Tel: +353 (01) 802 7173

Email: info@ridgeway-online.com
 Web: www.ridgeway-online.com